

I claim:

1. A shower device for attaching to a shower pipe, comprising:

a first region;

a second region in communication with said first region;

10 a porting region constricting the end of said second region;

a third region in communication with said porting region;

an inlet in communication with said third region;

a tube attached to said inlet;

a solution apparatus in communication with said tube; and

15 a point of dispersal in communication with said third region.

2. A shower device as in claim 1, wherein said first region is cylindrical in shape.

3. A shower device as in claim 1, wherein said second region is conical in shape.

4. A shower device as in claim 1, wherein said inlet can intake solution.

5. A shower device as in claim 1, wherein said porting region increases the velocity of the
20 water.

6. A shower device as in claim 1, wherein said third region uses a venturi force to
combine solution from said solution apparatus with water exiting from said porting
region.

7. A shower device as in claim 1, wherein said solution apparatus has at least one solution
25 reservoir.

8. A shower device as in claim 7, wherein said at least one solution reservoir holds a

- 5 solution such as soap or shampoo.
9. A shower device as in claim 8, wherein said at least one solution reservoir has at least one aperture for release of said solution.
10. A shower device as in claim 9, wherein said at least one aperture is in communication with a supply hose.
- 10 11. A shower device as in claim 10, wherein said supply hose is attached to said tube, in communication with said inlet.